# GLITTER

## SPECIFICATIONS

| Composition | Average Thickness | Carrier | Certifications |
|---|---|---|---|
| PU | 350 microns | Adhesive polyester | OEKO TEX® STANDARD 100 17CX00039 CENTROCOT; REACH n° 1907/2006/EU; VEGANOK AZIENDA N. 1004 |

## APPLICATION INSTRUCTIONS

| Applies on | SUGGESTED CUTTING SETTINGS | | | TRANSFER SETTINGS | | | |
|---|---|---|---|---|---|---|---|
| | Blade | Pressure | Speed | Time | Temperature | Pressure | Peel |
| cotton, polyester, poly/cotton blends (not suited for treated and dye sublimated textiles) | 60° | 120 gf | 20 cm/sec | 15 seconds | 160°C (320°F) | Medium (2,5/3,5 bar) | hot/cold |

→ **Mirror cut the design**
→ **Weed excess material**
→ **Place the design on the garment**
→ **Heat apply at the conditions shown above**
→ **Peel carrier hot/cold**

**PRODUCT HIGHLIGHTS**
→ **over 45 colours available**
→ **perfect for trendy or fashion items**
→ **"WOW" effect**

**NOTE: We highly recommend to perform a test before launching a production.**

## CARE AND WASHING RECOMMENDATIONS

| Washing | Ironing | Tumble dry | Dry cleaning | Storage Shelf Life | Storage Temperature | Storage Conditions | Position |
|---|---|---|---|---|---|---|---|
| Up to 40°C, inside-out | YES inside-out | YES (cotton cycle) | YES | Up to 2 years | Between 18°C and 26°C | Away from sunlight and dust | Vertical |

→ **Wait 24 hours after the application before the first wash**
→ **Respect the textile recommendations**
→ **Do not bleach or use aggressive chemical agents**

**This document can be subject to variations. Updated versions are available on www.siser.com. For further information, please contact our sales office: info@siser.it**

Siser s.r.l.
Viale della Tecnica, 18
36100 Vicenza - Italy

Tel. +39 0444.287960
Fax +39 0444.287959
info@siser.it
www.siser.com

r.e.a. vi 171856
reg. imp. vi n° 14971
c.s. € 103.300 i.v.
p.iva 01591490246

TÜVRheinland CERTIFIED
Management System ISO 9001:2015 ISO 14001:2015
www.tuv.com ID 9105027958