

VELCUT



Heat transfer flock-film > for plotter-cutting



EVO

| | | | | | | | |
|-----------------|--|-----------------|--|----------------|--|----------------------------|--|
| White 01 | | Dark Pink 28 | | Navy Blue 07 | | Cool Grey 11 | |
| Lemon 02 | | Lavender 29 | | Anis 35 | | Dark Grey 39 | |
| Sunny Yellow 03 | | Purple 30 | | Lime Green 23 | | Anthracite 18 | |
| Orange 12 | | Dark Purple 31 | | Light Green 36 | | Black 06 | |
| Electric Red 04 | | Mint 34 | | Green 10 | | Neon Yellow Premium | |
| Red 05 | | Sky Blue 15 | | Khaki 37 | | Neon Bright Orange Premium | |
| Dark Red 26 | | Turquoise 20 | | Beige 16 | | Neon Orange Premium | |
| Bordeaux 17 | | Blue 32 | | Brown 22 | | Neon Pink Premium | |
| Pink 27 | | Pacific Blue 08 | | Chocolate 14 | | Neon Blue Premium | |
| Magenta 21 | | Royal Blue 09 | | Light Grey 19 | | Neon Green premium | |

TOUCH

| | | | | | | | |
|-----------|--|-----------------|--|-----------------|--|---------------|--|
| White 91 | | Orange 82 | | Pacific Blue 88 | | Light Grey 89 | |
| Lemon 92 | | Electric Red 94 | | Royal Blue 99 | | Cool Grey 81 | |
| Yellow 93 | | Red 95 | | Navy 97 | | Black 96 | |



Manufacturing processes and related products are protected by existing patents :
 FR 97 12921; EUR 98 402 542.9; US 6.224.707; FR 98 12862; EUR 99 402 398.4;
 US 6.249.297; FR 04 08625; FR 05 05379; FR 05 05380;
 international extensions and new applications pending.



Heat transfer flock-film > for plotter-cutting



VelCut is a high-quality heat sealable flock film for plotter-cutting. It has been for 25 years a confirmed best seller. Very easy to cut and weed, it comes in a wide range of colors.



VelCut ist ein hochwertiger heißsiegelfähiger Plotter-flock. Seit 25 Jahren einer unserer Bestseller. Sehr leicht zu schneiden und zu entgittern und in vielen brillanten Farben.



VelCut est un film flocké thermocollant de haute qualité, pour découpe par plotter. Notre bestseller depuis 25 ans. Très facile à découper et écheniller, il est disponible dans une large gamme de coloris.

Instructions

EVO

TOUCH

FEATURES



500 µ

300 µ



60 °C

CUTTING CONDITIONS



45 - 60 °

45 °

TRANSFER CONDITIONS



160 - 170 °C
320 - 340 °F



Low - Medium



17 - 15 sec



Warm peel

PACKAGING



50 cm (19 ")



25 m - 10 m - 5 m
(27.3 yd - 10.9 yd - 5.4 yd)